



IP SERVICES





Home IP Services

Biblio. Data

Int. Class.:

PatentScope

Patent Search



Search result: 1 of 1

(WO/2003/011967) CURABLE COMPOSITION, CURED ARTICLE OBTAINED THEREFR(AND PHOTOCHROMIC OPTICAL MATERIAL AND PROCESS FOR PRODUCING THE SAME

National Phase

Latest bibliographic data on file with the International Bureau

Publication Number: WO/2003/011967

Publication Date: 13.02.2003

International Filing Date:

Chapter 2 Demand Filed: 18.11.2002

Claims

International Application No.: PCT/JP2002/002921

Notices

26.03.2002

Documents

C08F 220/36 (2006.01), C08F 230/08 (2006.01), C08G 18/81 (2006.01), C09D 4/00 (2006.01), G02B

5/23 (2006.01)

Description

Applicants: TOKUYAMA CORPORATION [JP/JP]; 1-1, Mikage-cho, Shunan-shi, Yamaquchi 745-0053 (JP) (All

Except US).

MOMODA, Junji [JP/JP]; do TOKUYAMA CORPORATION, 1-1, Mikage-cho, Shunan-shi, Yamaguchi

745-0053 (JP) (US Only).

MORI, Katsuhiro [JP/JP]; c/o TOKUYAMA CORPORATION, 1-1, Mikage-cho, Shunan-shi, Yamaguch

745-0053 (JP) (US Only).

Inventors:

MOMODA, Junji [JP/JP]; c/o TOKUYAMA CORPORATION, 1-1, Mikage-cho, Shunan-shi, Yamaguchi

745-0053 (JP).

MORI, Katsuhiro [JP/JP]; c/o TOKUYAMA CORPORATION, 1-1, Mikage-cho, Shunan-shi, Yamaguch

745-0053 (JP).

Agent:

OHSHIMA, Masataka; Ohshima Patent Office, Fukuya Bldg., 3, Yotsuya 4-chome, Shinjuku-ku, Tokyo

160-0004 (JP).

Priority Data: 2001-227374 27.07.2001 JP

2001-284521 19.09.2001 JP

Title:

CURABLE COMPOSITION, CURED ARTICLE OBTAINED THEREFROM, AND PHOTOCHROMIC

OPTICAL MATERIAL AND PROCESS FOR PRODUCING THE SAME

Abstract:

A useful curable composition giving a coating which has high adhesion to the substrate and to a hard coat layer and which has highly excellent photochromic properties, i.e., a high developed-color density, a high fading rate, and excellent durability. The composition comprises (1) 100 parts by weight of one

or more radical-polymerizable monomers comprising a silyl monomer such as

ϝ-methacryloyloxypropyltrimethoxysilane and/ or an isocyanate monomer such as a 2-isocyanatoethoxymethacrylate, (2) 0.01 to 20 parts by weight of an amine compound, and (3) 0.01 to 20 parts by weight of a photochromic compound. Applying this composition as a coating material to a resinous substrate gives a photochromic optical material which has excellent adhesion between the

photochromic coating layer and the substrate.

Designated AU, BR, CA, CN, IL, JP, KR, SG, US, ZA.

States:

European Patent Office (EPO) (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SI

Publication Language:

Japanese (JA)

Filing Language:

Japanese (JA)